

Website:- chemicalbull.com

MATERIAL SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name

Lithium Metal

CAS-No. : 7439-93-2

1.2 Relevant identified uses of the substance or mixture and uses advised against

: Laboratory chemicals, Manufacture of substances Identified uses

1.3 Details of the supplier of the safety data sheet

Company

:ChemicalBull Pvt Ltd 123/124, Panchratna, G.I.D.C Char Rasta, Vapi-396195 Dist, Valsad, Gujarat, INDIA Website: - chemicalbull.com

Email:- info@chemicalbull.com

1.4 Emergency telephone number

Emergency Phone +91 9696960250

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation

Substances, which in contact with water, emit flammable gases Skin corrosion

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation Pictogram



Signal word



Hazard statement(s)	
H260	In contact with water releases flammable gases which may ignite spontaneously.
H314	Causes severe skin burns and eye damage.
Precautionary statement(s)	
P223	Keep away from any possible contact with water, because of violent reaction and possible flash fire.
P231 + P232	Handle under inert gas. Protect from moisture.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P422	Store contents under inert gas.
Supplemental Hazard inform	nation (EU)
EUH014	Reacts violently with water.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula	:	Li
Molecular weight	:	6,94 g/mol
CAS-No.	:	7439-93-2

Component	Classification	Concentration
Lithium Metal		
	Water-react. 1; Skin Corr. 1B; H260, H314	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

- **4.2 Most important symptoms and effects, both acute and delayed** The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
- **4.3 Indication of any immediate medical attention and special treatment needed** No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use approved class D extinguishers or smother with dry sand, dry ground limestone, or dry clay.Dry powder

Unsuitable extinguishing media Do not use water, foam, or carbon dioxide.

- **5.2** Special hazards arising from the substance or mixture Lithium oxides
- **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.
- 5.4 Further information No data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust.

For personal protection see section 8.

6.2 Environmental precautions Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Do not flush with water. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of dust and aerosols. Provide appropriate exhaust ventilation at places where dust is formed. Keep away fromsources of ignition - No smoking. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Store under argon. Handle under argon. Store in cool place. Keep container tightly closed in a dry and well-ventilated place.

Never allow product to get in contact with water during storage.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of Regulation

Full contact Material: Nitrile rubber Minimum layer thickness: 0,11 mm Break through time: 480 min

If used in solution, or mixed with other substances, and under conditions which differ from, contact the supplier of the approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienistand safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a fullface particle respirator type N100 or type P3 respirator cartridges as backup to engineering controls. If the respirator is the sole means of protection, use a fullface supplied air respirator. Use respirators and components tested and approved under appropriate government standards

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: granular
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 180 °C - lit.
f)	Initial boiling point and boiling range	1.342 °C - lit.
g)	Flash point	Not applicable
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	1 hPa at 723 °C
I)	Vapour density	No data available
m)	Relative density	0,534 g/mL at 25 °C
n)	Water solubility	No data available
o)	Partition coefficient: n-octanol/water	No data available
p)	Auto-ignition	No data available

temperature

- q) Decomposition No data available temperature
- r) Viscosity No data available
- s) Explosive properties No data available
- t) Oxidizing properties No data available
- 9.2 Other safety information No data available

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No data available
- 10.2 Chemical stability

Stable under recommended storage conditions.

- **10.3 Possibility of hazardous reactions** Reacts violently with water.
- **10.4** Conditions to avoid Exposure to moisture
- **10.5 Incompatible materials** Forms shock-sensitive mixtures with certain

Forms shock-sensitive mixtures with certain other materials., Iron and iron salts., Heavy metals, Phosphorus, Sulphur compounds, Oxygen, Nickel, Do not store near acids., Metals

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Lithium oxides Other decomposition products - No data available In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity LD50 Intraperitoneal - Mouse - 1.000 mg/kg

Skin corrosion/irritation No data available

Serious eye damage/eye irritation No data available

Respiratory or skin sensitisation No data available

Germ cell mutagenicity No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

Additional Information

RTECS: 0J5540000

Large doses of lithium ion have caused dizziness and prostration, and can cause kidney damage if sodium intake is limited. Dehydration, weight loss, dermatological effects, and thyroid disturbances have been reported. Central nervous system effects that include slurred speech, blurred vision, sensory loss, ataxia, and convulsions may occur. Diarrhea, vomiting, and neuromuscular effects such as tremor, clonus, and hyperactive reflexes may occur as a result of repeated exposure to lithium ion., Cough, Shortness of breath, Headache, Nausea

SECTION 12: Ecological information

- **12.1 Toxicity** No data available
- **12.2 Persistence and degradability** No data available
- **12.3 Bioaccumulative potential** No data available
- **12.4 Mobility in soil** No data available
- 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECT	SECTION 14: Transport information		
SECI	Section 14: mansport mormation		
14.1	UN number ADR/RID: 1415	IMDG: 1415	IATA: 1415
14.2	UN proper shipping name ADR/RID: LITHIUM IMDG: LITHIUM IATA: Lithium Passenger Aircraft: Not permit	tted for transport	
14.3	Transport hazard class(es) ADR/RID: 4.3	IMDG: 4.3	IATA: 4.3
14.4	Packaging group ADR/RID: I	IMDG: I	IATA: I
14.5	Environmental hazards ADR/RID: no	IMDG Marine pollutant: no	IATA: no
14.6	Special precautions for use No data available	r	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety datasheet complies with the requirements of Regulation

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

EUH014	Reacts violently with water.
H260	In contact with water releases flammable gases which may ignite
	spontaneously.
H314	Causes severe skin burns and eye damage.

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. ChemicalBull Pvt Ltd and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product.

See chemicalbull.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale. The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches theproduct ordered. For further information please contact info@chemicalbull.com